

EVOLVE

SMART HANDHELD DEVICE



BUILT FOR BUSINESS AND MISSION-CRITICAL ENVIRONMENTS

The evolve smart handheld device combines intuitive user experience and open platform architecture with the ruggedness and reliability expected of a critical communications device. Evolve enables seamless communications across different locations and use on an exclusive spectrum (CBRS)

Evolve is also available in an intrinsically safe model for users who need reliable communications in hazardous environments.¹

EVOLVE AT A GLANCE

2 MODELS AVAILABLE

- Standard model
- Intrinsically safe model¹

RESILIENT AND RUGGED

- Dustproof and submersible IP68
- Glove operable touch screen
- Built to withstand repeated drops
- Long life and replaceable battery

SEAMLESS CONNECTIVITY

- 3G, 4G, Wi-Fi
- Dual SIM capability
- Ideal companion for WAVE PTX™

MISSION-CRITICAL

- Dedicated emergency and PTT buttons
- Loud, clear audio
- MIL-STD-810

OPEN ARCHITECTURE

- Android platform
- Open app ecosystem
- Centralized device management

INTUITIVE USER EXPERIENCE

- Simple interface
- 5" touch screen
- Front and rear facing cameras

HARDWARE	
Models	Standard model Intrinsically safe model ¹
Display	5.0 in (127 mm), 1280 x 720 px Capacitive touch-screen with Corning® Gorilla® Glass 3
Memory	4 GB RAM 64 GB Internal Storage Storage is expandable with external 128 GB microSD™ card
Camera	Rear 13 MP Auto focus High-output LED flash Digital zoom Front 8 MP
Built In sensors	Proximity sensor Ambient light sensor Accelerometer Barometer Gyroscope E-Compass
Ports	Micro USB 2.5 mm audio jack
Knobs/Buttons	Dedicated PTT button Dedicated emergency button Talkgroup rocker switch 3 programmable buttons Volume knob with power switch Home, Back and Recent buttons
Charging	Contacts on side, micro USB
SIM	2 x micro-3FF, dual SIM (DSDS)
PHYSICAL	
Dimensions (HxWxD)	Standard model with standard battery: 6.06 x 3.07 x 0.73 in 154 x 78 x 18.5 mm Standard model with high-capacity battery: 6.06 x 3.07 x 0.89 in 154 x 78 x 22.5 mm Intrinsically safe model ¹ with high-capacity Hazloc battery: 6.06 x 3.07 x 0.89 in 154 x 78 x 22.5 mm
Weight	Standard model with standard battery: 11.8 oz (333 g) Standard model with high-capacity battery: 13.9 oz (395 g) Intrinsically safe model ¹ with high-capacity Hazloc battery: 13.9 oz (395 g)

CONNECTIVITY	
LTE Bands	1, 2, 3, 4, 5, 7, 8, 12, 13, 17, 19, 20, 21, 28, 42, 43, 48 UMTS: 1, 2, 5, 8
Supported WCDMA	1, 2, 5, 8
Bluetooth	Bluetooth 5.0 + LE + BR/EDR
Location	GNSS (GPS, Galileo and Glonass), BeiDou and AGPS
Wi-Fi	2.4 GHz and 5 GHz
Wi-Fi Standard	802.11 a/b/g/n/ac/r/k/v
Wi-Fi Hotspot Band	2.4 GHz
SOFTWARE	
Operating System	Android™ 10.0 Android Enterprise
Google Mobility Services	Enabled
VIDEO AND IMAGING	
Supported File Types	MPEG4, H.264, MP3, AAC, AMR, JPG, PNG, GIF Encode Type: MPEG4, H.264-MP, H.265 (HW Accelerated)
Supported Formats	Decode Type: H.265 Video Param: H.264-BP, H.264-MP, MPEG-SP (VGA to 1080p HD, @60fps at minimum) Supported for playback, streaming, and recording
Supported File Types	3GPP (.3gp), MPEG-4 (.mp4), WebM (.webm), (.mkv)
Video Recording Quality	1080p (FHD) at 60 fps
AUDIO	
Input	Three microphones for superior noise suppression and echo cancellation
Output	2W top-rear-firing loudspeaker Loudness level: 97 dB Phon at 30 cm
Audio Formats	AMR-NB/WB, AAC-LC (96-128 kbps), EVS

BATTERY	
Capacity	Standard model with standard battery: 2900 mAh Standard model with High Capacity battery: 5800 mAh Intrinsically safe model ¹ with high- capacity Hazloc battery: 5800 mAh
SECURITY	
Root Detection	Standard
Multi-Factor Authentication	Optional
Mobile Virtual Private Network	Optional
Remote Configuration	Trusted 3rd party provided
OTA Firmware and Software Upgrades	Trusted 3rd party provided
Allowed Application List	Trusted 3rd party provided
Over-the-Air Wipe and Lock	Trusted 3rd party provided
Integrity Monitoring	Standard
Malware Blocking	Standard
ENVIRONMENTAL	
Operating Temperature	Standard model 14°F to 140°F (-10°C to +60°C) Intrinsically safe model ¹ -4°F to 140°F (-20°C to +60°C)
Storage Temperature	-40°F to 185°F (-40°C to +85°C)
Ruggedness	IP68 (2 metres underwater for 2 hours with AJ/USB/Battery covers fully closed) MIL-STD-810G
INTRINSICALLY SAFE MODEL FOR HAZARDOUS LOCATIONS	
Gas Hazardous Locations Classification Rating	Class I, Division 1, Groups C, D; Class I, Division 2, Groups A, B, C, D
TAMB Temperature	-4°F to +140° F (-20°C to +60°C)
Dust Hazardous Locations Classification Rating	Class II, Division 1, Groups E,F,G Class III
TAMB Temperature	-4°F to +140° F (-20°C to +60°C)

¹ When using the intrinsically safe Evolve model and Motorola Solutions UL approved battery, the intrinsically safe Evolve model is UL approved to 913_5 for use in Hazardous Locations. Classification Rating Class I, Division 1, Groups C, D; Class II Group E, F, G; Class III and Class I, Division 2, Groups A, B, C, D. T3C. Tamb = -4°F to +140° F (-20°C to +60°C)



EVOLVE SMART HANDHELD DEVICE

For more information, please visit commtechnw.com/product/evolve-lte-handheld/

COMM-TECH, INC. 100 North Morain Street, Suite 208 Kennewick, WA 99336 commtechnw.com

COMM-TECH, INC. is a family/veteran owned and operated business headquartered in Kennewick, Washington.

Choose COMM-TECH, INC. to bring a reliable two-way radio communication system to your business.

© 2023 COMM-TECH, INC. All rights reserved. 10-23